## APPLICATION FOR PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF NEVADA

THIS SPAC	E FOR OFFICE USE ONLY
Date of filing in State Engineer's Office	JL 2 9 2009
Returned to applicant for correction	
	Map filed FEB 1 0 2000 under
	6 5 8 7 <b>0</b>
The applicantRuby Pipeline, LLC., c/o Dan G. Gre	edvig
P.O. Box 1087	Colorado Springs
Colorado80944	hereby make(s) application for permission to appropriate
•	names of members.)
	Name of stream, lake, underground, spring or other sources.
2. The amount of water applied for is5.5	7 cfs (43.82 af)second feet. One second foot equals 448.83 gallons per minute.
(a) if stored in reservoir give number of acre-feet.	
3. The water to be used forPipelin  Irrigation, power, mining, c	ne Construction
4. If use if for:	•
(a) Irrigation, state number of acres to be irrigated	
(b) Stockwater, state number and kind of animals	
(c) Other use (describe fully under No. 12)Hydros	static testing and dust control
(d) Power:	
(1) Horsepower developed	
(2) Point of rature in ventor to stream	

to a found section corner. If on unsurveyed land, it should be so stated.)  NW1/4 SE1/4 Soc 26 T 45 N P 10 E A 4DD 8.44	t a point from which the pww corner of said Sec 26 bears S. 46°
	the proposed POD, use map on file under 66095/45없다
	me proposed FOD, use map on the under occost www.co.w
6. Place of use: (Describe by legal subdivision. If on unsurveyed land,	it should be so stated.)
T.42 N., R.21 E., portions of Secs 1, 2, 3, 4 and 5; T.43 N.	., R.21 E., portions of Secs 31, 32 and 33; T.42 N., R.20 E
portions of Secs 1, 2, 3 and 4; T.43 N., R.20 E., portions o	of Secs 7, 18, 19, 20, 28, 29 and 33; T.43 N., R.19 E., portions
of Secs 1 and 12; T.44 N., R.19 E., portions of Secs 3, 10,	14, 15, 23, 26, 35 and 36; T.45 N., R.19 E., portions of Secs 5, 6
.8, 16, 17, 21, 28, 33 and 34; T.46 N., R.19 E., portions of	Secs30 and 31; T.46 N., R.18 E., portions of Secs 2, 11,
.12, 13, 24 and 25; T.47 N. R.18 E., portions of Secs 15,	22, 26, 27, and 35. All MDB&MFor a map of proposed
	outDecember 31 <sup>st</sup> of each year
Month and Day	Month and Day
wen with pump and motor, etc.)	manner in which water is to he diverted, i.e. diversion structure, ditches, and flumes, drill
Existing 16" well, 550 feet deep	
0. Estimated time required to construct works: co	omplete(If well completed, describe works.)
10. Estimated time required to construct works:	water to beneficial use:two (2) years nd its water usage (use attachments if necessary):
10. Estimated time required to construct works:	water to beneficial use:two (2) yearsnd its water usage (use attachments if necessary):
10. Estimated time required to construct works:	water to beneficial use:two (2) years
10. Estimated time required to construct works:	water to beneficial use:two (2) yearsnd its water usage (use attachments if necessary):
10. Estimated time required to construct works:	water to beneficial use:two (2) years
10. Estimated time required to construct works:	water to beneficial use:two (2) years
10. Estimated time required to construct works:	water to beneficial use:two (2) years
O. Estimated time required to construct works:	water to beneficial use:two (2) years
O. Estimated time required to construct works:	complete
10. Estimated time required to construct works:	complete
O. Estimated time required to construct works:	complete
10. Estimated time required to construct works:	complete
10. Estimated time required to construct works:	complete
10. Estimated time required to construct works:	
10. Estimated time required to construct works:	(If well completed, describe works.)  water to beneficial use:two (2) years  nd its water usage (use attachments if necessary):

## EXHIBIT "A'

This application is one of several to provide construction water for compaction, dust control and hydrostatic testing. The total project consists of 670 miles of 42 inch Natural Gas Pipeline from Opal, Wyoming to Malin, Oregon passing through Elko Co., Humboldt Co. and Washoe County Nevada. This application is being filed pursuant to NRS 533.371 for a maximum of 2 years and shall expire upon completion of the project. The diversion rate on some of the applications is unusually high because during the hydrostatic test they need to fill the pipe as quickly as possible.